

## CTN Aluminum Standard Cylinder

### Specification

<b>Bore(mm)</b>	<b>50</b>	<b>63</b>	<b>80</b>	<b>100</b>
<b>Media</b>	Air			
<b>Operating Pressure Range</b>	0.9 ~9.9Kgf/cm <sup>2</sup>			
<b>Proof Pressure</b>	15Kgf/cm <sup>2</sup>			
<b>Ambient Temperature</b>	-5°C~+60°C (Not Freezing)			
<b>Sensor Switch</b>	RCA			
<b>Sensor Switch Holder</b>	HV2			HV4

### Stroke

<b>Bore(mm)</b>	<b>Standard Stroke</b>
<b>50</b>	50 100 150 200 250 300 350 400 450 500 600 700 800 900 1000
<b>63</b>	50 100 150 200 250 300 350 400 450 500 600 700 800 900 1000
<b>80</b>	50 100 150 200 250 300 350 400 450 500 600 700 800 900 1000
<b>100</b>	50 100 150 200 250 300 350 400 450 500 600 700 800 900 1000

### Ordering Code

CTN    —    50    ×    50    —    S    —    CA

<b>Type</b>	<b>Cylinder Bore</b>	<b>Stroke</b>	<b>Magnet Code</b>	<b>Accessory</b>

Blank: without magnet

CA: Aluminum

S: With magnet

CB: Cast iron

Pin: Used with CB