

MSQ Series Rotary Cylinder

Specification

Type	MSQB		
Acting	Double		
Dia(mm)	16	20	25
Port	PT 1/8		
Fluid	Air		
Pressure	1 ~ 99 kgf/cm ²		
Temperature	-5°C ~ +60°C		
Lubricator	without		
Cushion	NBR shock absorb or stopper		
Adjustable Angle	90°		
Sanser	RCD		

Cylinder Theory Output Sheet

Bore(mm)		16	20	25
Operating Pressure	0.1	0.24(0.02)	0.50(0.05)	0.98(0.1)
	0.2	0.48(0.05)	1.01(0.1)	1.96(0.2)
	0.3	0.72(0.07)	1.51(0.15)	2.95(0.3)
	0.4	0.96(0.1)	2.01(0.2)	3.93(0.4)
	0.5	1.21(0.12)	2.51(0.25)	4.91(0.5)
	0.6	1.45(0.15)	3.02(0.3)	5.89(0.6)
	0.7	1.69(0.17)	3.52(0.35)	6.87(0.7)

Ordering Code

MSQB	—	20	×	30	—	20	—	S
Type		Cylinder Bore		Stroke		Adjustable Stroke		Magnet Code
						10: 10 mm		Blank: Without magnet
						20: 20 mm		S: With magnet
						30: 30 mm		